

DIVISION PRODUCT CATALOG



### lodel 1030

- For upholstery pre-spray and spot treatments
- Indestructible spray gun
- Tip shut-off prevents dripping from tip
- Unique valve hanger for easy storage
- Safety lock prevents accidental discharge
   Quality brass fan tip included

- Viton® equipped
   Use for solvent or water based protectors, wall washing, neutralizing chemicals



ORDER CODE	MODEL#	CAPACITY	EXTENSION	NOZZLE	HOSE	WT. LBS.
12021030	1030	1 Gallon	_	Adjustable	40"	6
12011800	10-P	1 Gallon	12" Poly	Adjustable	30"	3.6
12011900	20-P	2 Gallon	12" Poly	Adjustable	30"	4.3
12012000	30-P	3 Gallon	18" Poly	Adjustable	30"	4.8
12011829	10-PV	1 Gallon	12" Poly	Adjustable	30"	4.0
12012150	20-PV	2 Gallon	12" Poly	Adjustable & Fan	30"	4.4
12012160	30-PV	3 Gallon	18" Poly	Adjustable & Fan	30"	4.8
12012200	1-PB	1 Gallon	12" Brass	Adjustable & Fan	40"	3.6
12012300	2-PB	2 Gallon	12" Brass	Adjustable & Fan	40"	4.5
12012400	3-PB	3 Gallon	18" Brass	Adjustable & Fan	40"	4.9
Vis. 8: istandard of Donat Bufance Flat.						

Viton® is a registered trademark of Dupont Performance Elastomers.

# **DuraSpray**

- Buna gaskets and sealsPoly shut-off and extension
- Adjustable pin-to-cone spray tip
- Transparent tank
- Heavy-duty poly tank
  Funnel top for easy filling
  Chemical resistant hose



10-P

# DuraSpray V

- Viton® gaskets and seals
- Poly shut-off and extension
- Adjustable pin-to-cone spray tip
- Fan spray tip
- Heavy-duty poly tankFunnel top for easy filling



#### Industria

- Viton® gaskets and seals
  Sturdy brass extension
- Adjustable pin-to-cone spray tip

10-PV

- Fan spray tip
   Heavy-duty poly tank
   Funnel top for easy filling
- Chemical resistant hose



# **Acid Sprayer**

- Poly molded thick wall polyethylene tank design
- · Adjustable pin-to-cone and optional fan spray tip
- Heavy-duty stainless steel pump rod
- Specially designed heavy-duty valve
- No metal parts come into contact with acid
- Valve locks on for continuous spraying



1-AS

# Chemical Resistant

3-AS

- Poly molded thick wall polyethylene tank design
- Celcon fan spray tip, brass fan tip kits available
- Viton® parts for excellent chemical resistance
- All brass XR gun
- Heavy-duty metal pump rod
- Celcon tips with variable output available



### Handheld Units

- Heavy-duty translucent tank to see liquid level
- Metal pump rod
- Large volume pump requires fewer pump strokes
- Economically priced
- Adjustable poly nozzle

- 1.5 Liter capacity
- No metal parts come in contact with acids
- Adjustable nozzle pin-to-cone and straight stream

- Viton® parts for excellent chemical resistance
- Translucent tank
- Steel pump rod
- Extended nozzle lance
- Adjustable brass nozzle
- Acid-resistant parts available

- Viton® components
- 6' coiled hose
- Half liter capacity
- Includes adjustable fine spray tip
  • Optional tips available
- Carry pouch included
- Highly efficient pump
- Heavy duty design



#### **SpotSprayR**

- Heavy-duty construction
- Chemical resistant seals
- All metal bottle with brass
- spray tip

   Adjustable pin-to-cone tip
- High efficiency pumpChemical resistant high wear belt holster included
- Economical yet durable



ORDER CODE	MODEL#	CAPACITY	EXTENSION	NOZZLE	HOSE	WT. LBS.
12012900	1-AS	1 Gallon	14" Poly	Adjustable	40"	3.8
12013000	2-AS	2 Gallon	14" Poly	Adjustable	40"	4.3
12013100	3-AS	3 Gallon	14" Poly	Adjustable	40"	4.9
12013600	1-CR	1 Gallon	18" Brass	Fan	40"	4.0
12013700	2-CR	2 Gallon	18" Brass	Fan	40"	4.8
12013800	3-CR	3 Gallon	18" Brass	Fan	40"	5.0
17017414	LT-1.5	1.5 Liter	_	Adjustable Brass	_	1.0
17017437	LT-1.5A	1.5 Liter	_	Adjustable Poly	_	1.0
17017401	QT-1	1.3 Quart	_	Adjustable Brass	_	1.4
24000110	AccuSpray I	.5 Liter	_	Adjustable	_	1
24000107	SpotSprayR		_	Adjustable Brass		

Viton® is a registered trademark of Dupont Performance Elastomers

**DuraSpray** 

- Funnel top for easy fillingChemical resistant hose
- Heavy-duty stainless steel
- Viton® seals and gaskets
- Valve locks on for
- constant spraying Valve locks off to prevent accidental discharge
- Adjustable pin-to-cone tip
- Deluxe fan tip kit available



### Carpet

#### Stain Protection Sprayer

- Extenda-Ban valve
- Chemical resistant hose
- Heavy-duty stainless steel
- Positive tip shut off
- Highly chemical resistant seals



#### Industrial

- Includes pin-to-cone tip and fan spray tip
- Valve locks on for constant spraying
- Braided chemical resistant hose
- Deluxe fan tip kit available
- Valve locks off to prevent accidental discharge
- Funnel top for easy filling
- Heavy-duty stainless steel
- Viton<sup>®</sup> seals and gaskets



2SPB

#### ORDER CODE MODEL # CAPACITY EXTENSION NOZZLE 12012100 20-S 2 Gallon 12" Poly Adiustable 2 Gallon 12" Brass Adjustable & Fan 40" 12012500 3 Gallon 18" Brass Adjustable & Fan 40' 12012600 6.6 2 Gallon 18" Brass 12013900 2-SCR 12014000 3-SCR 3 Gallon 18" Brass Fan 1 Gallon 18" Brass Fan

Viton® is a registered trademark of Dupont Performance Elastomers.

### Chemical Resistant

- Funnel top for easy filling
- Heavy-duty stainless steel
- Includes Celcon fan spray tip
- Viton® seals and gaskets
- Chemical resistant hose
- Durable brass XR gun



2SCR

### Private Labe

- Promote your company name on the world's best selling professional sprayer
- Minimum order is only 50 sprayers
- B&G sprayers will outlast and outperform any
- sprayer you've ever used. We guarantee it!
   For additional information call B&G Customer



## Sealer/Form Oil

• Includes brass tips for sealers and 35% solids

• Heavy-duty cast metal pump handle Heavy density polyethylene tank • Funnel top for easy filling

• Fully repairable pump design Chémical resistant hose

Viton® seals and gaskets

• 18" angled brass extension



#### Acetone

- 4' professional grade chemical resistant hose
- Adjustable pin-to-cone and fan spray tip
- Heavy density polyethylene tank
- Prevents accidental discharge

1.5HD

- Fully repairable pump design18" angled brass extension
- Heavy-duty metal pump rodPositive tip shut off





303HD

ORDER CODE	MODEL#	CAPACITY	EXTENSION	NOZZLE	HOSE	WT. LBS.
12012029	303HD	3 Gallon	18" Brass	Brass Fan	40"	7.4
17017409	1.5HD	1.5 Quart	_	Adj. Brass	_	1.4
12012113	401	1 Gallon	12" Poly	Fan	40"	3.6
12012112	402	2 Gallon	12" Poly	Fan	40"	4.3
12012064	403	3 Gallon	18" Poly	Fan	40"	6.4
12012422	503	3 Gallon	18" Brass	Brass Fan	40"	5.6
12013808	603	3 Gallon	18" Brass	Brass Fan	40"	5.7
12014006	803	3 Gallon	18" Brass	Brass Fan	30"	9.7
Viton® is a registered trademark of Dupont Performance Flastomers						

### Stainless Concrete

• Heavy-duty cast metal pump handle





- No metal parts come in contact with acid
- Includes pin-to-cone and fan spray tip
- Heavy density polyethylene tank
- Braided chemical resistant hose
- Fully repairable pump designViton® seals and gaskets
- 18" angled poly extension
- Stainless steel pump rod



### Concrete

- Heavy density polyethylene tank
- Brass fan spray tip #8004 included
- Braided chemical resistant hose
- Poly resin comfort grip handle18" angled poly extension
- Heavy-duty pump rod



- Tip shut off for drip free application
- Dual position handle (right or left)
- Deluxe comfort shoulder strap
- Piston pump mechanism
- Durable XR valve
- All exclusive "No Leak" pump design. Pump is enclosed in tank and prevents chemical leakage on the operator which is common with other backpacks.



ORDER CODE	MODEL#	CAPACITY	EXT./MOTOR	NOZZLE	HOSE 1	WT. LBS.
15015000	2300	1.5 Gallon	Two Stage	Fixed	_	11
15015100	2400	1.5 Gallon	Two Stage	Adjustable	_	12
15014901	2600	1.5 Gallon	Two Stage	Adjustable	18"	13
12014250	PestPro IV	4 Gallon	_	Fan*	_	_
12014249	Pest Pro II	2 Gallon	_	Fan	_	
*8004 fan and pin-to-cone tips included						

- All Foggers Feature

   Seamless, rotationally molded for maximum strength and lifelong durability
- Made of corrosion resistant materials for use with many chemicals

  1.5 Gallon capacity with 3-1/2" wide
- tank opening for easy filling and emptying

  Motors available in both 110V/60Hz
- or 220/240V
- Low profile for maximum stability
- Two stage motor

# My-Ti Lite 2300 • Preset delivery of 9 oz./minute

- Power mister
- Discharges liquid as wet fog that settles quickly
- Handles both water-based and oil-based liquids



#### **Jltra-Lite 2400**

- Adjustable flow rate up to 9 oz./minute
- Heavy-duty motor for reliability
  Handles both water-based and oil-based liquids
- Uses ULV delivery method for small micron droplets
- Use for disinfectants, deodorizers, and insecticides



### Flex-A-Lite 2600

- Uses ULV delivery method for small micron droplets
- Adjustable flow rate up to 18 oz./minute
  Use for disinfectants, deodorizers, and insecticides
- Nozzle mounted on 18" hose
- 24" & 48" hose available
- Handles both water-based and oil-based liquids



#### Anileator™

- No dangerous liquid fuels or pressurized tanks required
- Low maintenance
- Spill- and leak-proof tank
- Easy operation and nothing to adjust
- Quiet, electric operation
- Rubberized, non-slip handle
- Chemical/water resistance switch cover
- · Adjustable tilting head for multi-angle spraying



SPECIFICATIONS	
Tank diameter:	10 in (25.4 cm)
Machine height:	14 in (35.6 cm)
Tank capacity:	1 gallon (3.8 liters
Weight (Empty):	6.6 lbs (3.0 ka)

### Sani-Tizer™

#### Electric Portable Aerosol Applicator (ULV / Mister)

- Dispenses both oil and water-based products
- Specifically designed to spray anti bacterial agents at a droplet size targeted to kill the living virus on surfaces
- Solid brass metering valve for delivering precise outputs and maximizing use of chemicals
- Low profile tank design virtually eliminates tipping . . . empty or full
- Droplet sizes can be controlled for both ULV spraying and residual spraying

 Rugged design handles corrosive liquids and heavy impacts

#### SPECIFICATIONS

Adjustable 0-4.5 gal/hr, or 0-17 liters/hr Particle size: 5-50 microns (VMD) Tank capacity: 1 gallon (3.8 liters)



- Stainless steel pulse-jet engine
- Rugged chemical-resistant polyethylene
- formulation and fuel tanks

  Dispenses both petroleum and water-based products
- Patented 12 volt electric starting system
- No pressurized gasoline tank required



ORDER #	MODEL#	DESCRIPTION
62225-1	2997	Anileator 110 Volt
62225-2	2998	Anileator 220 Volt
62175-1	3001-1	Sani-Tizer 110 Volt
62175-2	3001-2	Sani-Tizer 220 Volt
43200	_	Trailblazer Electric Start
62150-3	3001-5 Hurricane ES 110V	110/120 volt AC, 6.8 Amps, 50/60 Hz
62150-4	3001-6 Hurricane ES 220V	220/240 volt AC, 3.4 Amps, 50/60 Hz

### Hurricane ES™

#### Portable Electrostatic Aerosol Applicator (ULV / Mister)

- Utilizes proven electrostatic technology to charge each droplet to provide effective application of formulations. The droplets stay separated due to the charged nature allowing uniform, even coverage on entire target surface every time.
- Dispenses water-based products
- Ideal for use in spraying commercial and residential areas
- Precision flow rate and droplet control
- Uniform and consistent coverage
- Droplet size can be controlled for both ULV and residual spraying
- Stainless steel metering valve

SPECIFICATION:	S
Adjustable	
flow rates:	0-9 oz/min (0-266 ml/min)
Particle size:	5-50 microns (VMD)
Tank capacity:	1 gallon (3.8 liters)
Length:	11.5 in or 29.2 cm
Width:	10 in or 25.4 cm
Height:	14 in or 35.6 cm
Weight (Empty):	7.5 lbs or 3.4 kg





